

# MOORING BUOY

## MB-2500



MB-2500-S-60T

**Diameter: 2.5m**

**Volume: 5.25m<sup>3</sup>**

**For workboat, large yacht and harbour**

*A mooring buoy with a polyethylene float requires less maintenance, less logistical resources and offers a longer service life than steel models.*

- 4 segments of float in precompounded low density virgin polyethylene, a material that is fully recyclable and does not need anti-fouling coating
- Central structure in steel with approved anti-corrosion system (galvanization, painting, anodes)
- Designed by GISMAN as per user requirements (site conditions, type of vessels...) and mooring calculation in conformance with international standards (DNV and API RP 2SK)

### 2.5M DIAMETER FLOAT

5.25m<sup>3</sup> volume

### ADDITIONAL CHARACTERISTICS

**Net buoyancy (L)**

4250

**Draught (m)**

1.1

**Submergence (kg/cm)**

50.3

**Total height (m)**

2.6

**SWL (tons)**

17 to 150

**Configurations**

«D»-link, «S»-Shakle,  
«CT» Chain Through or «T»-Static T.

### OPTIONS

Foaming with high density Polystyrene (EPS) or Polyurethane (PU)  
Retro-reflective stripes  
Identification/Marking with long life stickers  
Hand rail  
Rubber fender  
LED lantern  
Special Mark

